



Natural drying with fresh air

Our 300 AirDry Dishwasher finishes each cycle with a breath of fresh air, performing 3x better than closed-door systems. The door opens automatically during the drying phase using fresh air to get plates and cutlery completely dry.

Product Benefits & Features



Run your dishwasher whenever it suits you

This dishwasher gets to work when you want it to. With its Delay Start function, you can load it when you want to and program it to start at the time that suits your schedule. You can delay the start by up to 24 hours.



Spotless and sparkling, in every cycle

Our AutoFlex programme with smart sensor adjusts the consumption of each dishwashing cycle to the size and cleanliness of every load. Using only what is needed so that all dishes emerge spotless. No wasted water, energy or time. Just efficiently sparkling, every time.



Fast and efficient performance

For when you have a light load, the 30-minute quick wash programme of the dishwasher offers a timesaving solution with perfect washing results.

- Glass protection program
- Water sensor detects the level of dirt and adjusts water consumption
- Indications for salt and rinse aid
- Thermo Efficient System
- Text/symbol panel
- Dishwasher
- Waterstop System
- Inverter motor
- Installation
- Energy efficiency (2010/30/EC): A+
- Water and energy consumption
- Lower basket with 2 foldable plate racks
- Noise level: only 45 (dB(A) re 1 pW) (2010/30/EC)
- Delay start option from 1 to 24 hours
- Noise level: only 45 dB
- Indications for Delay start 1h-24h|Drying phase|HygienePlus|Program selected|Rinse aid|Salt|Washing phase|XtraDry
- Appliance HxWxD (mm): 850 x 600 x 625
- Dishwasher programmes: AutoFlex 45°-70°|Eco 50°|GlassCare 45°|Intensive 70°|QuickPlus 60°|Rinse & Hold
- Electrolux Free-standing Full-width Dishwasher ESF5513LOX

Product Specification

Color	Stainless steel
Installation type	Free-standing
Dimensions WxDxH in mm	W600 x D625 x H850
Drying Performance	A
Cleaning Performance	A
Energy class	A
Declared program	Eco 50
Net Weight (Kg)	43.85
Door colour	Stainless steel
Connected Load	1950
Required Fuse	10
Energy consumption Annual (kWh)	228.6
Number of IEC Place Settings	13
Panel colour	Stainless steel
Voltage (V)	220-240
Country of origin	PL