



### Your everyday, dried with care

Our excellent PerfectCare 600 tumble dryer with SensiCare System identifies the moisture level of each load using special sensors and adjusts the drying time accordingly. Meaning even the smallest load is never exposed to too much heat.


## Product Benefits & Features



### Less time, more care

Our SensiCare System adjusts the drying time to the moisture levels in each load. Saving time and energy without compromising on care.

- Special drying programs
- Feet
- Reverse tumble action loosens the clothes and prevents tangling and creasing
- Delay start option
- Appliance HxWxD (mm): 850 x 596 x 630
- Inverter motor technology
- Condense tank position and capacity
- Display type
- Indications for
- Door hinge
- Program card languages
- Dryer
- Sensor dryer
- Additional time controlled drying programs
- Full load capacity
- Drying status indication for



### Your style, your schedule

Our Delay Start helps you adjust the start of the drying cycle to suit your schedule. Simply enter the time you would like drying to automatically start and leave the machine to do the rest.



### Set the angle of your door to suit

The door on the Electrolux tumble dryer can be cleverly adjusted during installation to open at four different positions. Meaning the best possible fit with your other appliances, whether they are stacked on top of each other or adjacent to one another.

### Delicates, now dried gently

With our Delicate Option even delicates can be entrusted to the drum. The programme reduces the temperature in the chosen cycle to provide gentle care during drying.

### Your style, dried effortlessly

The extra-large door ensures everything can be accommodated with ease, even oversized or heavy garments.

**Product Specification**

Drying capacity (kg)	8.0
Color	White
Cord length (m)	1.45
Frequency (Hz)	50
Net Weight (Kg)	37.96
Voltage (V)	220-240
Motor system	Inverter
Required Fuse	13
Dryer Type	Condenser
Panel color	White
Dimensions WxDxH in mm	W596 x D630 x H850
Connected Load	2800
Average condensation efficiency, %	81